100 SERIES / CG23-M SINGLE ENDED BEAM MOUNT



100 SERIES - SINGLE ENDED BEAM MOUNT



OVERVIEW

The CG-23M is designed for use in light to medium capacity tanks, hoppers, and conveyors. The unique spherical washer design combines multidirectional movement with self checking capabilities.

Sold in Alloy Steel with Mild Steel Mount, Stainless Steel with Stainless Steel Mount, or Stainless Steel Welded Load Cell with Stainless Steel Mount.



NTEP CERTIFIED

Certificate of Conformance #08-074A1

CAPACITIES

250lb, 500lb, 1k, 1.5K, 2K, 2.5K, 4K, 5KSE, 5k, 10K

1 (800) 230-0120

contact@inscaleusa.com www.inscaleusa.com CAGE Code 07GT5

Nationwide Dealer Network

139

100 SERIES - SINGLE ENDED BEAM MOUNT

The CG-23M is designed for use in light to medium capacity tanks, hoppers, and conveyors. The unique spherical washer design combines multidirectional movement with self checking capabilities. Sold in Alloy Steel with Mild Steel Mount, Stainless Steel with Stainless Steel Mount, or Stainless Steel Welded Load Cell with Stainless Steel Mount.

PERFORMANCE SPECIFICATIONS

Safe Overload: 150% FS Full Scale Output: 3.00 mV/V Excitation Voltage: 10-15V AC/DC Load Cell Resistance: 350 ohms Load Cell Cable: 4 Conductor, 20ft Operating Temperature Range: -20° C to +60° C


Materials:


Load Cell: Alloy Steel (Nickel Plated) or Stainless Steel Assembly Cell: Alloy Steel (Nickel Plated) or Stainless Steel

Tolerances unless otherwise specified: .XX: ± 0.01 .XXX: ± 0.005 Fractions: $\pm 1/16$ " Angles: $\pm 1/2$ "

DIMENSIONS

	А	В	С	D	E	F	G
25lb - 5KSE	7.00"	5.00"	5.00"	2.00"	4.00"	0.50"	0.62"
5K - 10K	8.00"	6.50"	5.00"	3.00"	4.00"	0.50"	0.62"





100 SERIES - SINGLE ENDED BEAM MOUNT



